

LEDLine Luminaires

LEDLine Fit Slim 8

LLFS8

Linear luminaire



PRODUCT CODE EXPANSION

PCB & LED
Işık rengi / Light Color
Jack / connector/soket
IP koruma sınıfı / IP class
Montaj / Mounting

LLFS8-**P-C-J-I-M**

LLFS8 LUMINAIRE LED OPTIONS

TopLED

LLFS8 T40: 24V DC - 3W/m* - 300Lm

LLFS8 T60: 24V DC - 4,5W/m** - 450Lm

Big TopLED Mono Color

LLFS8 BT60:24V DC - 12W/m** - 1.200Lm

* Maximum length of this product, when supply is administered from a single location, is 2.4 meters.

**Maximum length of this product, when supply is administered from a single location, is 4.8 meters.




APPLICATION AREAS

LEDLine FS8, designed to be used in luminaires or applications such as behind glass, light box and PVC stretch ceiling.

ELECTROMECHANICAL SPECIFICATIONS LLFS8 P-C-J-I-M

- Anodized aluminium housing
- As standard, produced in 120 cm dimensions.
- PCB types can also be produced in custom dimensions according to cutting sizes.
- Luminaires are designed to be operative at 24V DC, as standard.



*All of the measurements for LEDLine product groups are in mm.

LIGHT COLOUR OPTIONS

LLFS8-P- C- J-I-M

C	CW: Cold White - 4.700K-9.500K	C	R: Red - 625nm
	NW: Natural White - 3.700K-4.700K		A: Amber - 590nm
	WW: Warm White - 2.700K-3.700K		G: Green - 525nm
			B: Blue - 465nm

SOCKET OPTIONS

LLFS8-P-C- J- I-M

- Luminaire has cabled and socket options.



J	K: Cable
	S: Cable Socket
	I : IP Cable Socket

Protection Class: IP20 / IP44 / IP66

Lifetime: 50.000 hours